



Description

ABAS Protect offers a complete assortment of chain link fencing, straight from our own assembly line. Since 1925, chain link fencing is at the core of ABAS Protect's product line.

Swedish industrial "standard" stipulates 2 meter high chain link fence with a mesh size of 50 x 50 mm, 3 mm steel wire, and three rows of barbed wire as top extension to prevent unauthorized access, in full compliance with Swedish insurance regulations.

Fence is manufactured in heights ranging from 600 mm to 4000 mm, with mesh sizes from 20 x 20 mm to 60 x 60 mm, and with wire sizes from 2.0 mm to 4.0 mm.

To ensure a long lifespan, the wire is hot-dip galvanized and optionally plastic coated. Fence posts are made of welded steel tubes in dimensions 50 x 50 mm or 60 x 60 mm, with diameter and thickness \varnothing 44 x 1.5 mm. All posts are hot-dip galvanized, or optionally Sendzimir processed with powder coating, enabling ABAS Protect's products to withstand high stress in lateral loads and also climate related impact.

Struts come in dimensions \varnothing 44 x 1.5 mm, in tubes 3500 mm long, and are flattened at one end. Standard colors include moss green (RAL 6005), olive green (RAL 6003) and black (RAL 9005).

Facts

Height:	600–4000 mm
Mesh size:	20, 30, 40, 50, 60 mm
Wire size:	2.0–4.0 mm
Treatment:	Hot-dip galvanizing
Color (coating):	moss green, olive green, black

Accessories

Mid posts:	50x50x1.5 mm
Corner posts:	60x60x1.5 mm
End posts:	60x60x1.5 mm
Struts:	\varnothing 44x1.5 mm
Miscellaneous:	Strut sleeve, tension wire, barbed wire, post feet, and more.

Fence posts are delivered with plastic cover, rivets and staples. Posts and struts are available in colors matching the fence.

Industrial fence is also available in security classes Sec 2 (ProNet welded panel fence), Sec 3 (ProFence palissade fence) and Sec4 (custom-tailored high security fence).