

ProSite mobile sliding gate



Description

ProSite is a cantilever sliding gate for temporary or permanent setup, with clear opening up to 6 m. The gate comes with an integrated concrete foundation, and is simply put on the ground as is. Connect with 230 V eurostyle connector and the gate is ready to operate. Control system and engine are integrated into the gate frame.

The gate leaf is made of steel profiles and runs on 2 twin wheels, C-profile 89 x 100 mm. Ground clearance is approximately 100 mm. Gate leaf and stand are hot-dip galvanized according to EN ISO 1461, C-section is pre-galvanized.

Security

ProSite has safety edge strips on back and front, as well as on the four sides of the gate stand. The gate is also equipped with interior and exterior stop buttons.

Add construction fence and our mobile rotor turnstile RTD to create a complete perimeter protection ready for ID06 and similar standards.

Facts

Clear opening:	< 6 m
Height:	2.4 m
Weight:	3500 kg, lifting points on gate and thrust block
Top extension:	Shark teeth
Filling:	Profiles 25x25 mm
Treatment:	Hot-dip galvanized
Drive:	Gear rack
Anti-trap protection:	Yes
Stop buttons:	Interior/exterior
Radio control:	Yes

Accessories

- Strobe light
- Rotating beacons
- Key control device
- GSM controller
- Access control system