

# ProGate Bas sliding gate



## Description

ProGate Bas is a cantilever single or double wing sliding gate with clear opening 4–8 meters per wing. The framework spans from 6515 to 11515 mm and is based on profiles.

The gate ledger, a 95x85 mm C profile, represents in combination with the framework the foundation. Gate stand and double back fence are made of hot-dip galvanized steel profiles.

## Security

Stop buttons for safety are placed at the interior and exterior of the gate. Safety edge strips on the gate front edge and backside of the gate frame are active at closing, strips on the front of the gate stand and the backside of the gate frame are active when opening.

The gate also has overload protection to protect the gate and engine when closing and opening, as well as motor protection in case gate operation is unusually heavy. Limited run time protects the engine from wear in case of malfunction.

Photocells reverse gate operation when closing the gate if cells are activated, and the gate opens fully. The gate can not be closed if the photocells are blocked. Vehicle loop detection can optionally be installed on the gate.

## Technical data

Height:	2.4 m
Clear opening:	4–8 m, 1 m interval
Top extension:	Shark tooth
Surface treatment:	Hot-dip galvanizing
Filling:	Profiles 25x25 mm
Safety edges:	Yes
Stop buttons:	Yes, interior/exterior
Radio control:	Yes
Photocells:	Yes

## Accessories

GSM control, access control, timer, code lock, proximity lock, flash light, vehicle loop detection, key control device etc.

ProGate Bas is factory installed and is mounted on a pre-cast concrete foundation. CE certification of the gate is carried out by ABAS Protect AB.

Note! Foundation is not included in the delivery. We always supply foundation blue prints for orders.