

ProGate Pro sliding gate



Description

ProGate Pro is a cantilever single or double wing sliding gate with clear opening 4–12 meters per wing. The framework spans from 7245 to 16285 mm and is based on profiles.

The gate ledger, a 160x150 mm C profile, represents in combination with the framework the foundation. Gate stand and double back fences in slick design are made of stainless steel with an illuminated exterior to accentuate the gate elegance at night.

Security

Stop buttons are placed at the interior and exterior of the gate, with the ability to resume operation automatically. Safety edge strips on the gate front edge are active at closing, strips on the gate stand are active when opening.

The gate also has overload protection to protect the gate and engine when closing and opening, as well as motor protection in case gate operation is unusually heavy. Limited run time protects the engine from wear in case of malfunction.

Photocells reverse gate operation when closing the gate if the cells are activated, and the gate opens fully. The gate cannot be closed if the photocells are blocked. Vehicle loop detection can optionally be installed on the gate.

Technical data

Height:	2.4 m
Clear opening:	4–12 m, 1 m interval
Top extension:	Shark tooth
Surface treatment:	Hot-dip galvanizing
Filling:	Profiles 25x25 mm
Safety edges:	Yes
Stop buttons:	Yes, interior/exterior
Radio transmitter:	Yes
Photocells:	Yes

Accessories

GSM control, radio control, access control, timer, code lock, proximity lock, traffic lights, rotating beacon, flash light, audio signal, vehicle loop detection, remote diagnosis, key control device.

ProGate Pro is factory installed and is mounted on a pre-cast concrete foundation. CE certification of the gate is carried out by ABAS Protect AB.

